

DF-Series LED-backlit Display 55"



**One Set Display,
Twice the Impact**



Featuring Full HD resolution and high brightness, the DF-Series is capable of delivering crisp images in diverse indoor environments. Dual HDMI connections make it easy to integrate IPCs or media players in order to display unique content on each screen. With a metal housing and movable floor stand, the DF-Series is ideal for a wide array of public environments.





Slim Metal Housing

With a 23.4mm amazingly slim profile, the DF-Series is shielded by a thin but highly-durable metal housing that creates a compact profile while ensuring safety and durability in public settings.

Multiple Media Playback Options

HDMI ports located on both the front and rear of the display allow you to incorporate either media players or IPCs to broadcast the media of your choice.



Music



Video



Images



Convenient Mobility

A free-standing, movable floor stand on removable casters makes the DF-series displays exceedingly agile.

Features

- Full HD 1920 x 1080 resolution
- 700 nits high brightness panels (front & back) fulfill diverse professional signage applications
- VA Panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles
- Dual-sided LCD signage with independent HDMI inputs
- Durable metal housing
- 23.4mm slim depth design
- Storage bay for media player / IPC
- Designed and developed for continuous 24/7 operation
- Free standing and movable floor stand

Specifications

DF-55

Panel

Panel Type	LED-Backlit TFT LCD (VA Technology)
Panel Size	54.6"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.630 mm
Brightness	700 cd/m ²
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07B
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 11%), 3H Hard Coating

Frequency

Frequency (H)	30 kHz-92 kHz
Frequency (V)	49 Hz-85 Hz

Signal Input

HDMI	1.4 x 2
------	---------

Power

Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	192W (On)
Stand-by Mode	< 2W
Off Mode	< 1W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)

Storage Conditions

Temperature	-10°C-50°C (14°F-122°F)
Humidity	20%-80% (non-condensing)

Dimensions

Product with Base (W x H x D)	952.7 x 2030.7 x 452.4 mm (37.5" x 79.9" x 17.8")
Packaging (W x H x D)	Box 1 1609.0 x 968.0 x 176.0 mm (63.4" x 38.1" x 6.9") Box 2 1068.0 x 735.0 x 400.0 mm (42.1" x 28.9" x 15.8")

Weight

Product with Base	94.5 kg (207.9 lb)
Packaging	Box 1: 48.0 kg (105.8 lb) Box 2: 62.0 kg (136.7 lb)

Regulation Approval

Certifications & Compliance	CE, CB, FCC, RoHS, WEEE, REACH, EAC
-----------------------------	-------------------------------------

Accessories

Supplied	Power Cord, Remote Control, Batteries
----------	---------------------------------------

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com