

DX-Series LED-backlit Display 55"



Dual-Sided Display



With Full HD resolution, 700-nits of brightness and a 4000:1 contrast ratio, the DX-55 display is able to perform impressively in diverse settings. Dual HDMI connections and ample space make IPC or media player integration easy. With a unique floating frame design and sturdy metal housing, DX-55 is another premium choice for retail locations, point of sale signage, and advertising in public environments.





An Elegant Artistic Design

The unique design of the DX-55, where the display seemingly floats in between two panes of glass, gives it a sleek, modern feel while the space below is ideal for placement of an IPC or media player.

Easy to Connect and Move

Dual HDMI connections for media players/PCs enable separately supplied video content. The free-standing, movable floor stand on removable casters allows for increased mobility.



High Visibility

With the brightness level that reaches 700 nits and VA technology that provides a wide viewing angle, the DX-55 is able to meet the visibility needs for semi-outdoor use.

Features

- Full HD 1920 x 1080 resolution
- VA Panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles
- Dual-sided LCD signage with independent HDMI inputs
- Glass protected floating frame design
- Durable metal housing
- Independent HDMI connections for separate content playback
- Free standing and movable floor stand
- Optional flight case (FTC-55E)



Specifications

DX-55

Panel	Panel Type	LED-Backlit TFT LCD (VA Technology)
	Panel Size	54.6"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.630 mm
	Brightness	700 cd/m ²
	Contrast Ratio	4000:1
	Viewing Angle (H/V)	178°/178°
	Display Colour	10.7B
	Response Time	5 ms
	Surface Treatment	Anti-Glare Treatment (Haze 11%), 3H Hard Coating
Frequency (H/V)	H Freq.	30 kHz-92 kHz
	V Freq.	49 Hz-85 Hz
Input	HDMI	1.4 x 2
Power	Power Supply	Internal
	Power Requirements	AC 100-240V, 50/60 Hz
	On Mode	192W (On)
	Stand-by Mode	< 2 W
Off Mode	< 1 W	
Glass	Thickness	4.0 mm (0.16")
	Reflection Rate	< 1%
	Transmission Rate	> 88%
	Hardness	> 7H
Operating Conditions	Temperature	0°C-40°C (32°F-104°F)
	Humidity	20%-80% (No condensation)
Storage Conditions	Temperature	-10°C-50°C (14°F-122°F)
	Humidity	20%-80% (No condensation)
Dimensions	w/Base	1011.6 x 2021.5 x 458.4 mm (39.8" x 79.6" x 18.0")
	Packaging (W x H x D)	1184.0 x 2207.0 x 666.0 mm (46.6" x 86.9" x 26.2")
Weight	w/Base	150.0 kg (330.7 lb)
	Packaging	160.0 kg (352.7 lb)
Regulation Approval	Certifications & Compliance	CB, CE, RoHS, WEEE, REACH
Accessories	Supplied	Power Cord

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com