

SQ-19



A value 19" surveillance display with rapid response time, quick signal-switching and robust connectivity for security and control centre environments.

With LED-backlit technology, the SQ-19 offers brilliant image and colour performance. Versatile input selection is designed to make system integration easy. The SQ-19 features auto NTSC/PAL detection, control key lock and auto setting adjustment which reduce maintenance hassle. Anti-Burn-in™ technology, quick signal-switching and rapid response time are provided to guarantee surveillance efficiency. The SQ-19 is designed for the trusted and affordable security and surveillance applications.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal settings
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -5° ~ 15°



SQ-19

Specifications

SQ-19

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	19.0"
	Max. Resolution	1280 x 1024
	Pixel Pitch	0.294 mm
	Brightness	250 cd/m ²
	Contrast Ratio	2,000,000 : 1
	Viewing Angle(H/V)	170°/160°
	Display Colour	16.7 M
	Response Time	3 ms
Horizontal Resolution	TV Lines	600TVL (NTSC/PAL)
Frequency (H/V)	H.Freq	30 kHz – 80 kHz
	V.Freq	50 Hz – 76 Hz
Input	VGA	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
Output	CVBS	BNC x 1
Audio	Audio In	3.5 Ø mm audio jack RCA L+R for video
	Audio Out	3.5 Ø mm audio jack
	Speaker	2 W x 2
Power	Power Supply	External
	Power Requirements	DC12V
	Consumption	25 W (On)
		0.5 W (Standby)
Plug and Play	VESA	EDID
Operating Conditions	Temperature	5°C ~ 35°C (41°F ~ 95°F)
	Humidity	20%~85%
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	5%~85%
Mounting	VESA FPM PMI	Yes (100 x 100 mm)
Tilt	Tile	-5° ~ 15°
Dimensions	Product (W x D x H)	411.0 x 183.0 x 410.0 mm (16.2" x 7.2" x 16.1")
	Packaging (W x D x H)	469.0 x 136.0 x 467.0 mm (18.5" x 5.3" x 18.3")
Weight	Product Weight (with base)	2.9 kg (6.4 lb)
	Packaging weight	4.1 kg (9.0 lb)
Regulation Approval	Certifications & Compliance	CE, FCC, CCC, CEL, RoHS, WEEE
Accessories	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC, video inputs allow multiple display connections



Video versatility, including VGA, HDMI, and BNC In/Out

