

PM-Series LCD Display 32" | 43" | 48" | 65"

Slim Bezel Displays for a Simple and Affordable Digital Signage Solution



The PM-Series slim bezel displays are designed for commercial applications that require the delivery of impactful content at a reduced total cost of operation. Given its easy-to-use content playback, Full HD resolution with a wide viewing angle, brightness of 350 nits and 16/7 reliability, these signage displays are the ideal solution for digital signage applications in restaurants, retail stores, medical offices, corporate meeting areas and hospitality.






Easily Deliver Business Messaging

The PM-Series combines Full HD 1920x1080 resolution, 350 nits of brightness and 16/7 commercial operation times to easily deliver business messaging and boost customer engagement.

Simple Content Scheduling

The embedded USB media player allows users to conveniently play content from a USB drive. Simply create scheduled playlists and configure playback settings with the included remote control to display your personalized content.



Versatile Connectivity

Easily connect a variety of devices with the versatile connectivity options including DisplayPort*, HDMI, DVI, USB, RS232 and RJ45.

PID Command & Ctrl Software

PID Command & Ctrl is a software that allows users to control AG Neovo displays via LAN or RS232 connections. It provides a simple and intuitive interface for remote management, OSD-related settings, and easy control on deployed displays. It also can be used to create video walls within minutes and assist system integrators with setting up displays.



Features

- Full HD 1920 x 1080 resolution
- Anti-Burn-in™ technology prevents image ghosting (48" & 65" only)
- DisplayPort 1.2 Multistream functionality allows for 4K UHD resolution across a 2x2 video wall (65" only)
- Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction
- Versatile connectivity: DisplayPort*, HDMI, DVI, VGA, Component, Composite
- An integrated scheduler allows content programming based on time and day
- Built-in USB media player for simple signage content delivery

- DMR function: play media shared over a local network
- RJ45, RS232, IR device control support
- Selectable gamma curves optimise different kinds of images
- OPS slot ready for easy media player / IPC integration (65" only)
- Built-in speakers
- Ideal for 16/7 commercial operation

* Features may vary by model

Specifications

PM-32

PM-43

Panel

Panel Type	LED-Backlit TFT LCD (IPS Technology)	LED-Backlit TFT LCD (VA Technology)
Panel Size	31.5"	42.5"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.364 mm	0.490 mm
Brightness	350 cd/m ²	350 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	178°/178°	178°/178°
Display Colour	16.7M	16.7M
Response Time	5 ms	5 ms
Surface Treatment	Anti-Glare Treatment (Haze <2%), 3H Hard Coating	Anti-Glare Treatment (Haze 2%), 3H Hard Coating

Frequency

Frequency (H)	31 kHz-92 kHz	31 kHz-92 kHz
Frequency (V)	48 Hz-85 Hz	48 Hz-85 Hz

Signal Input

HDMI	1.3b x 1	1.3b x 1
DVI	24-Pin DVI-D	24-Pin DVI-D
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1
Component	RCA x 1	RCA x 1
Composite	RCA x 1 (Share with Component-Y)	RCA x 1 (Share with Component-Y)

External Control

IR In	3.5 mm Phone Jack	3.5 mm Phone Jack
IR Out	3.5 mm Phone Jack	3.5 mm Phone Jack
RS232 In	2.5 mm Phone Jack	2.5 mm Phone Jack
RS232 Out	2.5 mm Phone Jack	2.5 mm Phone Jack
LAN	RJ45 x 1	RJ45 x 1

Other Connectivity

USB	2.0 x 1 (Service Port / Media Playback)	2.0 x 1 (Service Port / Media Playback)
-----	---	---

Audio

Audio In	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
Audio Out	Stereo Audio Jack (RCA)	Stereo Audio Jack (RCA)
Internal Speakers	10W x 2	10W x 2

Power

Power Supply	Internal	Internal
Power Requirements	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
On Mode	50W (On)	87W (On)
Stand-by Mode	< 0.5W	< 0.5W
Off Mode	< 0.5W	< 0.5W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)	20%-80% (non-condensing)

Storage Conditions

Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
Humidity	5%-90% (non-condensing)	5%-90% (non-condensing)

Mounting

VESA FPMPI	Yes (200 x 200 mm & 100 x 100 mm)	Yes (400 x 400 mm & 200 x 200 mm)
------------	-----------------------------------	-----------------------------------

Security

Kensington Security Slot	Yes	Yes
--------------------------	-----	-----

Dimensions

Product w/o Base (W x H x D)	726.5 x 425.4 x 65.1 mm (28.6" x 16.7" x 2.6")	968.2 x 559.4 x 59.9 mm (38.1" x 22.0" x 2.4")
Packaging (W x H x D)	818.0 x 547.0 x 139.0 mm (32.2" x 21.5" x 5.5")	1070.0 x 696.0 x 159.0 mm (42.1" x 27.4" x 6.3")

Weight

Product w/o Base	5.2 kg (11.5 lb)	8.7 kg (19.1 lb)
Packaging	7.8 kg (17.2 lb)	12.2 kg (26.9 lb)

Regulation Approval

Certifications & Compliance	FCC, CE, CB, WEEE, RoHS, REACH, EAC	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC
-----------------------------	-------------------------------------	---

Accessories

Supplied	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, CD	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, CD
----------	---	---

Optional Accessories

Floor Mount (Landscape only)	-	FMS-01, FMS-02, FMC-02
Ceiling Mount (Landscape only)	CMP-01+LMK-02, CMP-01+WMK-03	CMP-01+LMK-01, CMP-01+LMK-02, CMP-01+WMK-03
Wall Mount (Landscape only)	WMA-01, LMA-01, LMK-02, WMK-01, WMK-03, PMK-01	WMA-01, LMA-01, LMK-01, LMK-02, LMK-03, WMK-03
Desk Mount (Landscape only)	DMC-01, ES-02	DTS-01
Video Wall Mount (Landscape only)	-	VWM-01, VWM-02
Stand	STD-06	STD-07

Specifications	PM-48	PM-65P
Panel		
Panel Type	LED-Backlit TFT LCD (VA Technology)	LED-Backlit TFT LCD (VA Technology)
Panel Size	47.6"	64.5"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.549 mm	0.744 mm
Brightness	350 cd/m ²	350 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	178°/178°	178°/178°
Display Colour	1.07B	1.07B
Response Time	5 ms	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 2.3%), 2H Hard Coating	Anti-Glare Treatment (Haze 2%), 3H Hard Coating
Frequency		
Frequency (H)	31 kHz-92 kHz	31 kHz-92 kHz
Frequency (V)	48 Hz-85 Hz	48 Hz-85 Hz
Signal Input		
DisplayPort	-	1.2 x 1
HDMI	1.3b x 1	1.4b x 2
DVI	24-Pin DVI-D	24-Pin DVI-D
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1
Component	RCA x 1	BNC x 1
Composite	RCA x 1 (Share with Component-Y)	BNC x 1 (Share with Component-Y)
Signal Output		
DisplayPort	-	1.2 x 1
DVI	-	29-Pin DVI-I x 1 (VGA)
External Control		
IR In	3.5 mm Phone Jack	3.5 mm Phone Jack
IR Out	3.5 mm Phone Jack	3.5 mm Phone Jack
RS232 In	2.5 mm Phone Jack	2.5 mm Phone Jack
RS232 Out	2.5 mm Phone Jack	2.5 mm Phone Jack
LAN	RJ45 x 1	RJ45 x 1
RJ11	-	Yes
Other Connectivity		
USB	2.0 x 1 (Service Port / Media Playback)	2.0 x 1 (Service Port / Media Playback)
OPS Slot	-	Yes
Audio		
Audio In	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
Audio Out	Stereo Audio Jack (RCA)	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2	10W x 2
Speaker Output (RMS)	-	10W x 2
Power		
Power Supply	Internal	Internal
Power Requirements	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
On Mode	102W (On)	186W (On)
Stand-by Mode	< 0.5W	< 0.5W
Off Mode	< 0.5W	< 0.5W
Operating Conditions		
Temperature	5°- 40° (41°F-104°F)	0°-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)	20%-80% (non-condensing)
Storage Conditions		
Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
Humidity	5%-90% (non-condensing)	5%-90% (non-condensing)
Mounting		
VESA FPM/PMI	Yes (400 x 400 mm & 200 x 200 mm)	Yes (400 x 400 mm)
Security		
Kensington Security Slot	Yes	Yes
Dimensions		
Product w/o Base (W x H x D)	1081.8 x 623.4 x 59.9 mm (42.6" x 24.5" x 2.4")	1459.0 x 835.0 x 82.0 mm (57.4" x 32.9" x 3.2")
Packaging (W x H x D)	1192.0 x 773.0 x 171.0 mm (46.9" x 30.4" x 6.7")	1655.0 x 1078.0 x 280.0 mm (65.2" x 42.4" x 11.0")
Weight		
Product w/o Base	11.5 kg (25.4 lb)	24.8 kg (54.7 lb)
Packaging	16.4 kg (36.2 lb)	39.3 kg (86.6 lb)
Regulation Approval		
Certifications & Compliance	CCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC, FCC	CE, CB, WEEE, RoHS, REACH, EAC, FCC
Accessories		
Supplied	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, RS232 Daisy Chain Cable, CD	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, RS232 Daisy Chain Cable, CD
Optional Accessories		
Floor Mount (Landscape only)	FMS-01, FMS-02, FMC-02	FMC-03+LMK-04, FMC-04+LMK-04
Ceiling Mount (Landscape only)	CMP-01+LMK-01, CMP-01+LMK-02, CMP-01+WMK-03	CMP-01+LMK-01
Wall Mount (Landscape only)	WMA-01, LMA-01, LMK-01, LMK-02, LMK-03, WMK-03	LMA-01, LMK-01, LMK-03
Desk Mount (Landscape only)	DTS-01	DTS-01
Video Wall Mount (Landscape only)	VWM-01, VWM-02	VWM-01, VWM-02
Stand	STD-07	STD-08

All specifications are subject to change without prior notice.

Copyright © 2020 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.

All other trademarks are the property of their respective owners.

P/C: PM32A0/PM43A0/PM48A0/PM6PA0 Version 4.0, 20200520



Google Play is a trademark of Google, Inc.